Service

In our Dutch headquarters we have the repair and calibration facilities to support our products. Repair and calibration is carried out under the scope of the ISO 9001 certificate.

Contact Details

web. www.industrialphysics.com

email. info@industrialphysics.com

10-2024-V1

TQC Sheen is a brand of Industrial Physics Inc.

INDUSTRIAL PHYSICS

TQC sheen

TQC sheen

PGX+ Quick Start

INDUSTRIAL PHYSICS

Protecting product integrity

How to start:

The PGX control software can be installed from the supplied USB stick. The software is compatible with Windows, up to the latest version.

Consumables:

PG1023	Liquid container kit (with & w/o plug), 5+5 pcs
PG1171	Steel cannulus tip 0.5 mm (min order quantity 10 pcs)
PG1005	Pump tubing (steel tip) suitable for most liquids, 1 pcs
PG1026	Pump tubing (steel tip) suitable for most liquids, 5 pcs
PG1006	Pump tubing (PTFE tip) suitable for most liquids, 1 pcs
PG1021	Pump tubing (PTFE tip) suitable for most liquids, 5 pcs
PG1025	Applicator tubing between syringe and tubing dispenser, 10 pcs
PG1027	Pump tubing (Silicone) suitable for diiodomethane, 2 pcs

PG1023

PG1171

PG1005

PG1026

PG1006

PG1021

PG1025

PG1027

PGX+ dosing unit

The optional and stand alone dosing unit has advantages over the integrated dosing unit. The injection method used in the dosing unit allows testing with thicker fluids and dispenses a more consistent amount of fluid. The dosing unit is not only able to pump fluids but also to retract them.